



Sno-Pro II Plow

TTYP08PA32 • TTYP09PA32

www.flinkco.com

**FOR USE WITH ANY MAKE AND MODEL OF
CLASS 5 OR CLASS 6 VEHICLE**

**Special Design Features For Use On:
City Streets • Intersections • Parking Lots**



Manufactured by Flink Company

502 N. Vermillion St., Streator, IL 61364

Phone: (815) 673-4321 info@flinkco.com

A PROVEN LEADER IN ICE AND SNOW REMOVAL EQUIPMENT



www.flinkco.com

SPECIAL FEATURES

SNO-PRO II PLOW

MODEL	LENGTH OVERALL	HEIGHT	VERTICAL RIBS	BOTTOM ANGLE	CUTTING EDGE	MOLDBOARD THICKNESS
TTPY08PA32	8'	32"	2	4" x 4" x 1/2" x 96"	5/8" x 8" x 96"	3/8" Polymer
TTPY09PA32	9'	32"	2	4" x 4" x 1/2" x 108"	5/8" x 8" x 108"	3/8" Polymer

LIGHTWEIGHT



**FULLY
REMOVEABLE**

POLY-MOLDBOARD

**QUICK
DISCONNECT**

SPECIFICATIONS

MOLDBOARD: 3/8" thick ultra molecular weight polyethylene

PAINT: Black Powder Coat

A-FRAME: Reinforced end plate and pivot plate

TRIP EDGE MECHANISM: Bottom torsion trip assembly to be activated whenever there is an obstruction on the pavement contacted

SPRINGS: (6) .563 Round wire torsion springs

POWER ANGLE: (2) 2" x 10" Single Acting Cylinders

OPTIONS:

- TAPERED RESILIENT DEFLECTOR
- CUSHION VALVE
- CURB SHOES
- CUTTING EDGE SHOES

Manufactured by Flink Company
 502 N. Vermillion St., Streator, IL 61364
 Phone: (815) 673-4321 info@flinkco.com